

# Python PANDAS Code Bytes

This page contains brief (generally one-liner) blocks of code for working with Python and [PANDAS](#) for data analytics. I created it as a handy reference for PANDAS commands I tended to forget when I was learning. I hope it proves useful to you, too! I also have a page with longer [data analytics tutorials](#).

## Table of Contents

- [Jupyter Notebook Settings](#)
- [Working with Python Lists](#)
- [Working with Python Dictionaries](#)
- [Analysis](#)
- [Generating New Variables, Arrays, etc.](#)
- [I/O](#)
- [Looping](#)
  
- [Time Series](#)
- [Indexing and Sorting](#)
- [Missing Data](#)
- [Custom Functions](#)
- [DataFrame Manipulations](#)
- [Custom Twitter Variables](#)
- [Working with MongoDB in Python](#)

## Jupyter Notebook Settings

Set width of columns for display:

```
pd.set_option('display.max_columns', None)
```

Set cell width:

```
pd.set_option('max_colwidth', 150)
```

# Working with Python Lists

Break list into chunks of 4 (needed for some APIs, for example)

```
mylist_chunked = [mylist[i:i+4] for i in xrange(0, len(mylist), 4)]
```

Finding duplicates in a list:

```
import collections
mylist = ['twitter', 'facebook', 'instagram', 'twitter']
[item for item, count in collections.Counter(mylist).items()
if count > 1]
```

```
Remove list element:
mylist.remove('revenue')
```

# Working with Python Dictionaries

Delete a key from a dictionary:

```
del dict[key]['key_to_delete']
```

Create sub-dictionary (from sub-set of keys):

```
subdict = {k: dict[k] for k in ('key1', 'key2')}
```

# Analysis

Cross-tabulation:

```
pd.crosstab(df['var1'], df['var2'])
```

# Generating New Variables, Arrays, etc.

Create list from dataframe column:

```
screen_names = df['screen_name'].tolist()
```

Create list of unique column values in DF:

```
tickers_in_df = pd.unique(df.ticker.ravel()).tolist()
```

Convert string variable to float:

```
df['count_V2'] =
```

```
df['count'].convert_objects(convert_numeric=True)
```

Convert float column to int (only works if there are no missing values):

```

df_2014['rt_count'] = df_2014['rt_count'].astype(int)
    Convert column to string:
        df.index = df.index.astype(str)
    Create new variable as a slice of an existing one:
    df['cusip8'] = df['cusip'].apply(lambda x: x[:8])
    Replace a word within a column with another word:
df['8-K'] = df['8-K'].str.replace('Item', 'Section')
    Fill in missing values for one column with zero:
df_2014['rt_count'] = df_2014['rt_count'].fillna(0)
    Get new list of unique items in a list:
    screen_names_unique = list(set(screen_names))
Create dummy variable based on whether another column contains
specific text (values will be 'True' and 'False'):
    df['retweeted_status_dummy'] =
df['retweeted_status'].str.contains('THIS', na=False)
    Then convert to float (will convert 'True' and 'False'
categories of above variable into '1' and '0', respectively):
    df['retweeted_status_dummy'] =
    df['retweeted_status_dummy'].astype(float)
    Replace values (here, replace 'None' with '0'):
    df['reply_message'] =
df['in_reply_to_screen_name'].replace([None], ['0'])
    Replace values (here, replace np.nan values with '0'):
df.ix[df.Number_of_retweets.isnull(), 'Number_of_retweets'] =
    0
    Switch values of '0' and '1':
df['reply_message'] = df['reply_message'].replace([1],
    [99]).replace([0],[1]).replace([99],[0])
Create binary variable from count variable (if old var=0,
assign value of 0; otherwise 1):
df['urls'] = np.where(df['entities_urls_count']==0, 0, 1)
    Change each unicode element in a list to string:
tickers_in_df = [x.encode('UTF8') for x in tickers_in_df]
    Change column values to upper case:
df['Name'] = df['Name'].apply(lambda x: x.upper())
    Change column values to upper case:
sec['8-K Item'] = sec['8-K Item'].str.upper()
    Find number of unique values:
len(pd.unique(compustat_2013.cusip.ravel()))
Add leading zeros to string variable (as many as needed to
reach 10 characters):

```

```

df['cik_x'] = df['cik_x'].apply(lambda x: x.zfill(10))
    Convert column to string and add leading zeros:
df['CIK_10'] = df['CIK'].astype(str).apply(lambda x:
    x.zfill(10))
    Get a list of values from a DF column:
values_list = df['8-K'].value_counts().keys().tolist()
    Find number of cases with fewer than the mean value:
sum(df['followers_count'] < df['followers_count'].mean())

```

## I/O

```

    Read in a pickled dataframe:
ticker_master = pd.read_pickle('valid_tickers_317.pkl')
    Read in JSON file:
f = open('valid_tickers_list_317.json', 'r')
    valid_tickers = simplejson.load(f)
    Read in JSON file -- method 2:
with open('my_list.json', 'r') as fp:
    my_list = json.load(fp)
    Save a list as JSON file:
f = open('all_valid_screen_names.json', 'w')
simplejson.dump(valid_twitter_accounts, f)
    f.close()
    Save a list as JSON file -- method 2:
with open('my_list.json', 'w') as fp:
    json.dump(my_list, fp)
    Read in Excel file:
twitter_accounts = pd.read_excel('Twitter Account-level
Database – non-excluded tickers and accounts only.xlsx',
    'accounts', header=0)
    Write Excel file:
df.to_excel('df.xls', sheet_name='Sheet1')

```

## Looping

```

Looping over rows (note how to select a slice of rows):
for index, row in df[:10].iterrows():
    print index, row['content']
Loop over rows and update existing variable:
for index, row in df.iterrows():

```

```

df['count'] = count
Loop over rows and create new variable, method 1:
    for index, row in df.iterrows():
        #df.ix[df.index==index, 'count'] = count #LONGER
            VERSION
        df.ix[index, 'count'] = count #SHORTER VERSION
Loop over rows and create new variable, method 2:
    for index, row in df.iterrows():
        df.loc[index, 'count'] = count

```

## Time Series

```

Weekdays:
weekdays_only = by_day2[by_day2['weekday'] < 5 ] weekday_count
= df.groupby(ts.index.weekday).apply(f) by_day3['weekday'] =
    by_day['date'].apply(lambda x: x.weekday())
Add missing days (with zeros) for every day in a dataframe:
df_filled = df.unstack().fillna(0).stack()
Change specific columns
df_filled.loc[df_filled['Number of Firm Tweets'] == 0,
['Number of Firm Followers (start)', 'Number of Lists for Firm
(start)']] = np.nan
Set column to datetime:
df['created_at'] = pd.to_datetime(df['created_at'])
Convert datetime column to date:
df['date'] = [t.date() for t in df['datetime']]
Generate lagged variable with multi-index DF:
df['Mentions [t-1]'] =
df['Mentions'].unstack().shift(1).stack()
Generate variable aggregated over 3-day window lagged one day:
df['Mentions [sum of t-1:t-3]'] =
pd.rolling_sum(df['Mentions'].unstack().shift(),
window=3).stack()
Select date range for DF:
df_2014 = df['2014-1-1': '2014-12-31']

```

## Indexing and Sorting

```

Set the index:
df = df.set_index(['created_at'])

```

```

Reset Index:
df.reset_index(inplace=True)
Set Multi-Index:
df = df.set_index(['ticker', 'day'])
Sort dataframe:
df.sort(['ticker', 'day'], inplace=True)
Name Existing Multi-index columns:
df.index.names = ['day', 'ticker']
With multi-index df -- get unique items per index level:
len(firm_day_counts_firm_tweets.index.levels[0])
len(firm_day_counts_firm_tweets.index.levels[1])
Swap levels on multi-index dataframe:
df_swapped = df.swaplevel('ticker', 'day')
Get minimum date in DF:
df.index.min()
Complex conditional row selection during loop:
if (row['Form Type'] == '8-K') and (row['8-K Item']==") and
(row['8-K Item - V2']==") or (row['8-K Item']=='Item that') or
(row['8-K Item']=='Item fo'):

```

## Missing Data

```

Interpolation with backfill and forward fill (n.b. - does not
respect multi-index):
df['F_x')]=df['F'].interpolate(method='linear').bfill().ffill(
)
Find rows with empty column:
missing = df[df['ticker'].isnull()]
Fill missing values in one column with values from another
column:
sec.loc[sec['8-K Item_v2'].isnull(), '8-K Item_v2'] = sec['8-K
Item']

```

## Custom Functions

```

Function for generating a series of new one-day lag variables
in a dataframe:
def lag_one_day(df):
    #df_cols = df.columns
df_cols = [u'Number of Firm Mentions', u'Number of Firm

```

```

        Tweets']
        for i in df_cols:
            col = str(i)+str('[t-1]')
            if '[t-1]' not in str(i):
                df[col] = df[i].unstack().shift(1).stack()
Function for generating a series of new dataframe variables
that aggregate over a multi-day period:
def lag_one_day(df):
    #df_cols = df.columns
df_cols = [u'Number of Firm Mentions', u'Number of Firm
        Tweets']
        for i in df_cols:
            col = str(i)+str('[sum t-1:t-3]')
            if '[t-1]' not in str(i):
df[col] = pd.rolling_sum(df[i].unstack().shift(),
                        window=3).stack()

```

## DataFrame Manipulations

Subset of DF -- based on a condition in a column:

```
df[df['reply_message'] == 1]
```

Subset of DF -- specific columns:

```
df[['in_reply_to_screen_name', 'in_reply_to_status_id',
    'reply_message']].head()
```

Drop a column:

```
df = df.drop('entities_urls',1)
```

Intersection of two lists:

```
pd.Series(np.intersect1d(pd.Series(tickers_in_df),
    pd.Series(valid_tickers)))
```

Difference between two lists (all different elements from either list):

```
set(tickers_in_df).symmetric_difference(valid_tickers_with_twitter)
```

Difference between two lists (elements from list1 missing from list2):

```
set(list1) - set(list2)
```

Create DF based on whether column value is in a list:

```
df = df[df.ticker.isin(mylist)]
```

Creat an empty dataframe:

```
columns = ['ticker', 'month', 'degree']
df = pd.DataFrame(columns=columns)
```

```

    Add row (row 0) to empty dataframe:
df.loc[0] = pd.Series({'ticker':'Z', 'month':'12', 'degree':
    })
Change cell column values for a specific row (index=16458):
sec.ix[16458, "8-K Item – V2"] = 'Item 2.01'
Create dataframe from list/dictionary:
months = ['2014-1', '2014-2', '2104-3']
data = {'month': months}
df = pd.DataFrame(data, columns=['month', 'degree'])
Add rows to a dataframe:
df = df.append(df_month)
Create dataframe from list of column names:
d = {'Variable Name': list(df.columns.values)}
variables = DataFrame(d)
Create dataframe by deleting all rows with null values in one
column:
df2 = df[df['keep'].notnull()]
Rename a single column:
df.rename(columns={'cusip':'cusip_COMPUSTAT'}, inplace=True)
Create dataframe based on column value appearing in a list:
missing = df[df['cusip'].isin(mylist)]
Look for duplicates in a dataframe:
counts = merged.groupby('cusip').size()
df2 = pd.DataFrame(counts, columns = ['size'])
df2 = df2[df2.size>1]
df2
Create version of dataframe with conditions on two variables
(for removing a duplicate firm):
merged = merged[~((merged['fyear']==2012) &
    (merged['gvkey']=='176103'))]
Select partial dataframe -- complex conditions:
sec[(sec['Form Type'] == '8-K') & (sec['8-K Item']==") &
(sec['8-K Item – V2']==") | (sec['8-K Item']=='Item fo') &
(sec['8-K Item – V2']==") | (sec['8-K Item']=='Item that') &
(sec['8-K Item – V2']==")]
Merge two dataframes:
merged = pd.merge(fb, org_data, left_on='feed_id',
    right_on='Org_ID')
Deep copy of DF:
df2 = df.copy(deep=True)
Get a slice of dataframe (here, the two rows with the given

```



```
indexes):
df.loc[11516:11517]
```

## Custom Twitter Variables

```
Time on Twitter:
import datetime
df['start']=np.datetime64('2016-04-01')
df['created_at'] = pd.to_datetime(df['created_at'])
df['time_on_twitter'] = df['start'] - df['created_at']
df['time_on_twitter_days'] =
df['time_on_twitter'].astype('timedelta64[D]')
df['time_on_twitter_days'] =
df.time_on_twitter_days.astype('int')
```

## Working with MongoDB in PANDAS

```
Show first 2 documents:
for user in users.find():2]:
    print user, '\n'
Get frequency counts:
from bson.son import SON
pipeline = [ {"$group": {"_id": "$FormType", "count": {"$sum":
    1}}} ]
list(file_list.aggregate(pipeline))
Loop over random sample of 100 with filtering:
for file in file_list.aggregate([
    { '$match': {'FormType': { '$in': ['990PF']}} },
    { '$sample': {'size': 100} }
]):
    print file
```

I hope you have found this helpful. If so, please spread the word, and happy coding!